



**(12)**

**EUROPEAN PATENT SPECIFICATION**

**(45) Date of publication of patent specification :  
06.11.91 Bulletin 91/45**

**(51) Int. Cl.<sup>4</sup> : G01N 33/558, G01N 33/548**

**(21) Application number : 88303376.3**

**(22) Date of filing : 14.04.88**

**(54) Solid phase assay employing capillary flow.**

**(30) Priority : 13.05.87 US 49328**

**(73) Proprietor : Becton Dickinson and Company  
One Becton Drive  
Franklin Lakes New Jersey 07417-1880 (US)**

**(43) Date of publication of application :  
17.11.88 Bulletin 88/46**

**(72) Inventor : Rosenstein, Robert W.  
4273, Bright Way  
Elliott City, MD 21043 (US)  
Inventor : Bloomster, Timothy G.  
8, Brookebury Apt. 1C  
Reisterstown, MD 21136 (US)**

**(46) Publication of the grant of the patent :  
06.11.91 Bulletin 91/45**

**(84) Designated Contracting States :  
AT BE CH DE ES FR GB GR IT LI NL SE**

**(74) Representative : Lamb, John Baxter et al  
MARKS & CLERK 57-60 Lincoln's Inn Fields  
London WC2A 3LS (GB)**

**(56) References cited :  
EP-A- 0 154 749  
EP-A- 0 225 054  
EP-A- 0 255 342  
WO 86/04683**

**EP 0 291 176 B1**

Note : Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid (Art. 99(1) European patent convention).

## Description

This invention relates to an assay for an analyte, and more particularly to a solid phase assay.

In a solid phase assay, a binder specific for at least the ligand to be determined (analyte) is supported on a solid support, whereby, in the assay it is not necessary to employ an additional agent for separating the bound and free phases formed in the assay.

Assays for analytes wherein the tracer employed in the assay includes a particulate label, such as, for example, a liposome which includes a detectable marker are known in the art. Thus, for example, an assay is known wherein a binder specific to the analyte is supported on a solid support, and the tracer is comprised of a ligand specific for the analyte, which ligand of the tracer is labeled with a particulate label, such as a liposome containing a detectable marker. In such an assay, the tracer is indirectly bound to the binder on the solid support by binding of the analyte to the binder and binding of the tracer to the analyte, whereby the presence and/or amount of analyte in a sample can be determined by detecting the presence and/or amount of tracer, which is indirectly bound on the solid support. In such assays, as disclosed for example in EP-A-0225054 and WO-A-8604683, a sample solution and a tracer may be caused to flow, via a common path, to a binder containing position.

The present invention is directed to improving assays for an analyte wherein the binder is present on a solid support, and in particular wherein the tracer employed in the assay is comprised of a ligand labeled with a particulate label.

In accordance with one aspect of the present invention, there is provided an assay for an analyte wherein there is employed a solid support having first, second and third portions, with the third portion of the solid support including a binder for the analyte, with the sample being applied to the first portion of the solid support and tracer to the second portion of the solid support. The first and second portions of the solid support are in capillary flow communication through separate and distinct flow paths with the third portion of the solid support to provide for capillary flow of the sample and tracer for contact with the binder. The sample and tracer are caused to flow to the binder in a manner such that the sample contacts the binder in a manner such that the sample contacts the binder, prior to substantial contact of the tracer with either of the sample or binder.

The tracer is a ligand labeled with a detectable label, preferably a particulate label, with the ligand portion of the tracer capable of being bound directly or indirectly to analyte which is bound to the supported binder.

The amount and/or presence of analyte in a sample may be determined by detecting the presence and/or amount of tracer bound to the analyte, which

analyte is bound to the binder in the third portion of the solid support.

In accordance with another aspect of the present invention, there is provided a solid support having a first portion for receiving a tracer, a second portion for receiving a sample and a third portion which includes a binder for analyte in the sample wherein the first and second portions are both in capillary flow communication through separate and distinct flow paths with the third portion to provide for flow and contact between the tracer, sample and binder. The capillary flow communication is such that there is contact between sample and binder prior to substantial contact of the tracer with either the sample or the binder.

The tracer and sample are applied to separate portions of the solid support, without prior contact between the sample and the binder, with the sample and tracer flowing by capillary action to the third portion of the support, which contains supported binder for the analyte, in a manner such that the sample contacts the binder, prior to any substantial contact between the tracer and either of the sample or the binder, whereby a so called "sandwich assay" is accomplished, in the so called "forward" or "sequential" mode, without the necessity of separately directly applying a sample and tracer to the portion of the solid support which contains the supported binder.

The solid support includes an absorbent material capable of transporting a liquid by capillary flow. In this manner, the tracer and sample which are applied to separate portions of the support are transported by capillarity to the portion of the support which includes immobilized binder. As hereinabove indicated, the portion of the support to which the sample is applied, and the portion to which the tracer is applied are both in capillary flow communication with the portion of the support containing the immobilized binder in a manner such that the sample contacts the binder prior to substantial contact of the tracer with either the sample or the supported binder. Such a result may be achieved by appropriately arranging the respective portions of the support to which the sample and tracer are applied, with respect to the portion of the support to which the binder is applied, in a manner such that the path of travel of the sample to the binder is shorter than the path of travel of the tracer to the binder. In a preferred embodiment, the tracer has a detectable particulate label whereby the tracer, having a particulate label, moves at a slower rate than the sample, and such difference in flow rate, as well as any difference in flow path aids in providing for contact of the sample with the binder, prior to contact of the tracer with either the sample or the binder. It is to be understood, however, that the length of the flow path of the tracer may be the same or less than the length of the flow path of the sample to the binder in that it is possible to provide for prior contact of the sample with the binder by means other than the length of the respective flow

paths.

Thus, for example, a blocking agent may be added to the portion of the solid support which provides a capillary flow path between the portion of the support to which the tracer is applied, and the portion of the support which includes the binder to thereby impede the flow of the tracer to the binder. Such a blocking agent is a material which inhibits wetting of the support, with such inhibition of wetting reducing the rate at which the liquid containing the tracer flows by capillarity to the portion of the support including the supported binder. As representative examples of such blocking agents, there may be mentioned: bovine serum albumin, alone or in combination with glucose; other proteinaceous matter alone or in combination with a sugar such as for example a fish gelatin obtained from a fresh water fish in combination with sucrose. The selection of a suitable blocking agent which inhibits wetting of the absorbent material to reduce the rate of flow should be apparent to those skilled in the art from the teachings herein.

As further alternatives, the respective rates of flow may be controlled by the width of the respective flow paths or the area to which tracer and sample are applied.

It is also to be understood that a combination of various means may be employed to insure that the sample applied to the solid support reaches the binder, prior to contact between the tracer and the binder, such as, for example, a combination of respective lengths of flow path and the use of a blocking agent to inhibit the flow of the tracer.

Applicant has also found that substantial contact between the tracer and the sample, prior to contacting of the binder with the sample, should also be prevented. Applicant has found that prior contact between the sample and the tracer on the solid support may reduce sensitivity and/or may cause agglutination of the tracer in the preferred embodiment where the label of the tracer is a particulate label, whereby the sample and the tracer are applied to the separate portions of the solid support, which are in capillary flow communication with the portion of the support containing the binder, in a manner such that substantial contact between the tracer and the sample is avoided, prior to contacting of the sample with the binder. Such a result may be achieved by causing the sample to flow to the binder, ahead of the tracer, as hereinabove indicated. In addition, prevention of contact between sample and tracer prior to contact with the binder may be further assured by providing separate paths of flow for each of the sample and tracer.

Thus, the solid support is constructed and the portions to which the tracer and sample are applied are arranged in a manner such that both the tracer and the sample flow by capillary action through separate and distinct flow paths to the portion of the support which includes the binder and in a manner such that

the sample contacts the binder prior to any substantial contact of the tracer with either the binder or the sample. Such a result may be achieved by arranging the respective flow paths and/or flow rates of the sample and tracer on the support to achieve such a result, whereby both the sample and tracer may be applied to the support without the necessity of separately directly adding both sample and tracer to the portion of the support containing the immobilized binder.

At least the portion of the support which provides the capillary flow paths for the tracer and sample is formed from a suitable absorbent material which is capable of transporting a liquid by capillarity. As representative examples of such materials, there may be mentioned: glass fiber, cellulose, nylon, crosslinked dextran, various chromatographic papers, nitrocellulose, etc. The selection of a suitable material is deemed to be within the scope of those skilled in the art from the teachings herein.

In accordance with a particularly preferred embodiment, the portion of the support which includes the binder (third portion) is employed as the test area for determining bound tracer. In accordance with the particularly preferred embodiment, at least the third portion of the support is formed from a material which is capable of transporting material by capillary flow through such third portion and which has a surface area capable of supporting the binder in a concentration of at least  $1 \text{ ug/cm}^2$  (most generally in a concentration of at least  $10 \text{ ug/cm}^2$ ).

Although nitrocellulose is a preferred material, it is to be understood that other materials having a surface area sufficient for supporting the binder in a concentration as hereinabove described may also be employed for producing such solid supports.

In accordance with a particularly preferred embodiment, the pore size of the solid support is such that the preferred tracer (ligand labeled with a particulate label), when bound directly or indirectly to the analyte bound to the binder, remains on the surface of the support.

As should be apparent, portion of the support (or all of the support) in addition to the portion of the support employed for supporting the binder may be formed from a material having a surface area capable of supporting the binder in the hereinabove described concentrations.

The type of binder which is used in the assay is dependent upon the analyte to be assayed. As known in the art, the binder which is supported may be an antibody including monoclonal antibodies, an antigen, a protein specific for the material to be bound or a naturally occurring binder. If the assay is for an antibody, then the binder may be, for example, an antigen or an antibody which is specific for the antibody to be assayed. If the analyte is an antigen (an antigen having more than one determinant site), then the binder

may be an antibody or naturally occurring binder which is specific for the antigen to be assayed.

The selection of a suitable binder for support on the solid substrate is deemed to be within the scope of those skilled in the art from the teachings herein.

The ligand which is labeled for use as a tracer in the assay of the present invention is dependent upon the analyte to be assayed, as well as the assay procedure.

Thus, for example, the ligand may be specific for the analyte, whereby the tracer would be bound directly to the analyte which is bound to the supported binder. Alternatively, the ligand employed in forming the tracer may be one which is capable of being bound to an analyte specific for the analyte; e.g. the ligand tracer may be IgG labeled with a particulate label, whereby the tracer is indirectly bound to the analyte through an antibody bound to the analyte. As should be apparent, the ligand used in producing the tracer may be an antigen or an antibody or a naturally occurring substance which is specifically bound by the analyte. The selection of a suitable ligand is within the scope of those skilled in the art.

As hereinabove indicated, in producing the tracer, the ligand is preferably labeled with a particulate label, which includes a detectable marker. In accordance with a preferred embodiment, the particulate label is visible. A preferred particulate label is a sac, which includes a dye or other colored substance as a marker, whereby the tracer, when used in the assay, is visible without destruction of the sac to release the colored substance.

The sac which is used to label the ligand for producing a tracer may be any one of a wide variety of sacs, including but not limited to intact erythrocytes, erythrocyte ghosts, liposomes (single walled [sometimes called vesicles] or multilamellar), polymer microcapsules (for example, those made by coacervation, or interfacial polymerization), etc.

Erythrocyte ghosts are known in the art and are prepared by suspending erythrocyte cells in a solution of substantially lower osmolarity. The ghosts are "resealed" in an aqueous solution including the marker whereby the ghosts include the marker in the interior thereof. Such procedures are known in the art and the resealing solution of appropriate osmolarity generally includes, in addition to the marker, alkali and alkaline earth metal halides and coenzyme; e.g., adenosine triphosphate. The preparation of ghosts, as sacs, is disclosed, for example, by D'Orazio et al, *Analytical Chemistry*, Vol. 49, No. 13, pages 2083-86 (Nov. 1977).

Polymer microcapsules are also produced by procedures known in the art except that the solution in which the microcapsules are formed also includes the marker whereby the interior of the polymer microcapsule includes the marker. The preparation of such microcapsules is disclosed for example in *Microencap-*

*apsulation Process and Applications*, edited by Jan E. Vandegger (Plenum Press 1974).

As known in the art, liposome can be prepared from a wide variety of lipids, including phospholipids, glycolipids, steroids, relatively long chain alkyl esters; e.g., alkyl phosphates, fatty acid esters; e.g., lecithin, fatty amines and the like. A mixture of fatty materials may be employed, such as a combination of neutral steroid, a charged amphiphile and a phospholipid. As illustrative examples of phospholipids, there may be mentioned lecithin, sphingomyelin, dipalmitoyl, lecithin, and the like. As representative steroids, there may be mentioned cholesterol, cholestanol, lanosterol, and the like. As representative examples of charged amphiphilic compounds, which generally contain from 12 to 30 carbon atoms, there may be mentioned mono- or dialkyl phosphate ester or an alkylamine; e.g. dilauryl phosphate, and the like.

The liposome sacs are prepared in an aqueous solution including the marker whereby the sacs will include the marker in the interior thereof. The liposome sacs are easily prepared by vigorous agitation in the solution, followed by removal of marker from the exterior of the sac.

Further details with respect to the preparation of liposomes are set forth in U.S. Patent No. 4,342,826 and PCT International Publication No. WO80/01515.

As hereinabove indicated, the marker preferably included in the sac is a dye or some other material which is visible, without lysing of the sacs.

The tracer comprised of ligand and particulate label may also be produced by labeling the ligand with an aqueous dispersion of a hydrophobic dye or pigment, or of polymer nuclei coated with such a dye or pigment. Such labels are described in more detail in U.S. Patent No. 4,373,932, which issued on February 15, 1983. The tracers produced in accordance with such patent may also be employed as tracers in the present invention.

As indicated in the aforesaid patent, the colored organic compounds which are used as labels are in the form of a hydrophobic sol, which hydrophobic organic dyes or pigments are insoluble in water or soluble only to a very limited extent. As indicated in the patent, particles of the aqueous dispersion of a hydrophobic dye or pigment, or of polymeric nuclei coated with such a dye or pigment have a particle size of at least 5 nm, and preferably at least 10 nm.

Such tracers which are labeled with the hydrophobic dye or pigment or with a polymer nuclei coated with such dye or pigment, are visible tracers when used in the assay in accordance with the present invention.

The visible particulate label may be visible polymer particles, such as colored polystyrene particles, preferably of spherical shape.

As representative examples of other particulate

labels which may be employed in producing a tracer for use in the assay of the present invention, in which the tracer would be visible, there may be mentioned ; ferritin, phycocerythins or other phycobilli-proteins ; precipitated or insoluble metals or alloys ; fungal, algal, or bacterial pigments or derivatives such as bacterial chlorophylls ; plant materials or derivatives.

The ligand may be labeled with the particulate label so as to produce a tracer for use in the invention by procedures generally known in the art, with the procedure which is used being dependent upon the ligand and the particulate label which is employed. Such techniques include absorption, covalent coupling, derivatization or activation. In producing a tracer wherein the ligand is labeled with a sac, the sac may be produced from a component which has been derivatized with a ligand, whereby the sac, when produced, is sensitized with the ligand. In another procedure, the sac including the marker may be initially formed, followed by sensitizing the sac with ligand by procedures known in the art.

Thus, the preferred tracer is comprised of a ligand and a particulate label (solid or solid-like, as opposed to non-solid labels, such as radiostopes, enzymes and various fluorescent materials), and the particulate label preferably provides a tracer which is visible under the assay conditions so that the presence and/or amount of analyte may be determined without further treatment and without the use of instrumentation ; e.g. by use of a liposome containing a dye as the particulate label.

The solid substance employed in the assay is preferably in sheet form, with the substrate, in sheet form, generally being in the form of a card, a test strip or dipstick.

The binder is supported on the test area of the solid substrate by applying a solution of the binder to a defined area of the test substrate ; such as, for example, in the form of a spot, which can be located in a marked area, e.g. square or circle, on the substrate. Particularly good results have been obtained when the binder is applied to the test area as a spot having a diameter of from 3 to 5 mm. The concentration of the binder placed in the defined test area will vary depending upon the assay to be performed ; however, the binder is generally present in a concentration of at least  $1 \mu\text{g}/\text{cm}^2$  (most generally at least  $10 \mu\text{g}/\text{cm}^2$ ).

After application of the binder to one or more test areas on the substrate, the residual binding capacity of the test substance is saturated or blocked by treatment of the test substrate which one or more types of proteins which do not specifically bind the materials to be employed in the assay. Thus, for example, the residual binding capacity of the substrate may be blocked so as to prevent non-specific binding by the use of bovine serum albumin. The techniques for preventing non-specific binding are generally known in the art,

and such techniques are also generally applicable to preventing non-specific binding in the assay of the present invention.

In accordance with the present invention, the first portion of the solid support may be provided with the tracer, during the assay procedure, or the solid support may be produced with the tracer on the first portion thereof. In the latter case, the tracer is supported on the support in a manner such that upon wetting of the first portion, the tracer flows by capillarity to the third portion of the solid support. Thus, for example, the tracer may be absorbed on the solid support, in the first portion thereof, whereby upon wetting of the first portion during the assay, the tracer flows by capillarity to the third portion of the solid support which includes the binder, as hereinabove described.

The invention will be further described with respect to embodiments thereof illustrated in the accompanying drawings wherein :

Referring to Figure 1, there is shown a test card 10, which is generally comprised of an upper card member 11 and a lower card member 12. The upper card member 11 is provided with a tracer loading port 13, sample loading port 14 and a test view window or port 15. A test sheet 16, preferably nitrocellulose, is placed between the upper and lower card members 11 and 12, respectively, with a portion of the nitrocellulose being visible through test port 15. At least a portion of the sheet 16 which is viewable through window 15 includes a binder specific for the analyte to be assayed and defines a test area. A first strip of absorbent material 17 is placed between the upper and lower card members 11 and 12 and extends between tracer loading port 13 and view window 15 with the absorbent material 17 being in contact with test sheet 16. A second strip of absorbent material 18 is placed between the upper and lower card members 11 and 12 and extends between sample loading port 14 and view window 15, with the absorbent material 18 being in contact with the test sheet 16. As shown, the strips 17 and 18 are separate and distinct from each other and provide separate capillary flow paths from each of ports 13 and 14 to view window 15. Strips 17 and 18 may be formed, for example, from glass fiber.

As particularly shown, the sample loading port 14 is closer to the viewing window 15 than the tracer loading port 13, whereby the capillary flow path between ports 14 and 15 is shorter than the capillary flow path between ports 13 and 15. In addition, the strip 17 may be treated with a material to reduce the capillary rate of flow.

A piece of material 21 having a high liquid absorption capacity, such as blotting paper, is positioned between upper and lower card member 11 and 12 in contact with test sheet 16 to receive and store test material.

In an assay, a sample to be assayed is applied through test port 14 and tracer is applied through test

port 13. The sample flows to the test sheet 16 through strip 18 and the tracer flows to test sheet 16 through strip 17. As hereinabove indicated, the flow paths or strips are constructed in a manner such that the sample contacts the binder on the test sheet 16 prior to contact of the tracer with either the binder or sample. The tracer may then be determined through test window 15.

The presence and/or amount of analyte present in the sample may be determined by the presence and/or amount of tracer, as determined through window 15 of the card 10.

In accordance with a preferred embodiment, as hereinabove described, by using an appropriate material as sheet 16 (for example, nitrocellulose) and a visible particulate label (such as a liposome including a suitable dye), it is possible to determine tracer through window 15 without destruction of the liposome.

Although the embodiment has been described with respect to the use of a tracer which includes a visible particulate label, it is to be understood that other detectable labels may be employed; e.g. an enzyme label; a chromogen label (fluorescent and/or absorbing dye), etc. In such cases, it may be necessary to add an additional substance in order to detect the label in view window 15; e.g. in the case of an enzyme label, a substrate to produce detectable color in the view window.

It is also possible to provide a view window over the material 11 in place of or in conjunction with the view window 15. In this manner, tracer which has not been bound in test sheet portion 16 may be determined. The presence and/or amount of tracer in portion 21 may be employed to determine analyte along and/or in conjunction with the presence and/or amount of analyte in portion 16.

The invention will be further described with respect to the following example; however, the scope of the invention is not to be limited thereby:

#### EXAMPLE

A reaction card 10 was constructed using two plastic cards 11 and 12. The cards were made of polypropylene with a thickness of approximately 0.03 inches. The top card has three holes which include a view window 15, liposome tracer loading port 13, and a sample loading port 14. The view window has a diameter of approximately 12.0 mm while the loading ports are smaller (4.0 mm).

The first step in construction was to place double stick adhesive (3M Type 960) over the entire card. Nitrocellulose (5.0  $\mu$ m S & S) with the capture antibody was attached to the card as test sheet 16. Sheet 16 was spotted with 3  $\mu$ l of affinity purified rabbit anti-Group A *Streptococcus* antigen and then blocked with 3% bovine serum albumin. The antibody portion is

below window 15. Blotting paper 21 (Gelman 51334) was placed on the card such that the paper was in contact with the nitrocellulose. The window and loading ports were punched out of a second card. Adhesive was placed over the holes and excess adhesive was removed from the holes. This process led to a card that had adhesive completely surrounding the ports. Next, strips of glass fiber (Whatman GF/A) 17 and 18 were placed on the card such that they made a connection from the loading ports to the view window. Strip 18 is treated with a 3% BSA solution.

Detector liposomes packed with sulfo-rhodamine dye were prepared by the method outlined in O'Connell et al. (Clin. Chem. 31: 1424 [1985]). They were covalently coupled to affinity purified rabbit anti-Group A *Streptococcus* antigen.

Group A *Streptococcus* organisms were harvested from culture plates, washed with saline (0.9% NaCl), and adjusted to  $1 \times 10^6$  organisms/ml. An aliquot (0.1 ml) containing  $1 \times 10^6$  organisms was subjected to the micro nitrous acid extraction method for exposing the Group A carbohydrate antigen. This method consists of mixing 0.3 ml of 0.1 M HCl with 40  $\mu$ l of 4M NaNO<sub>2</sub>, adding this to the *Streptococcus* organisms and, after 3 minutes, neutralizing with 40  $\mu$ l of 1M Tris base. To facilitate the extraction, the HCl and the subsequent diluting fluid contain 0.1% Tween®-20 non-ionic detergent.

A reservoir was attached to the device to assure that all the sample (0.3 ml) could be added at one time. Immediately after addition of the sample through port 14 the liposome tracer was added to the tracer port 13. No other manipulations were required. Within five minutes a specific signal at the capture antibody spot (Window 15) could be seen at a sensitivity level equivalent to  $1 \times 10^4$  CFU/ml.

The present invention is advantageous in that it is possible to provide a sandwich assay without separate incubation and wash steps, and which has the requisite sensitivity.

These and other advantages should be apparent to those skilled in the art.

#### Claims

1. A method of assay for determining an analyte in a sample comprising:

providing a solid support (12) with a sample to be assayed, the solid support including a first portion (14, 18), a second portion (13, 17) and a third portion (15, 16), the third portion including a binder for the analyte, the first portion of the support receiving the sample, and the second portion receiving a tracer; moving tracer and sample by capillary flow, through separate and distinct flow paths, from the second and first portions to the third portion to firstly provide contact between sample and binder prior to substantial contact

of the tracer with either the sample or binder and then to provide contact between tracer, binder and sample to thereby provide a complex, in the third portion, of any analyte in the sample, binder and tracer; and determining tracer in the third portion of the support or tracer which has passed through the third portion of the support to determine analyte.

2. A method as claimed in claim 1 in which the tracer comprises a ligand and a particulate label.

3. A method claimed in claim 2 in which the particulate label is a liposome, including a coloured substance.

4. An article of manufacture for carrying out the method of claim 1, comprising :

a solid support (12) including first (18), second (17) and third (16) absorbent material portions, the first portion including a sample receiving portion (14), the second portion including a tracer receiving portion (13), the third portion including a binder for the analyte to be assayed, the third portion being in capillary flow communication with both the sample and tracer receiving portions to provide for capillary flow of sample and tracer to the third portion to provide contact between tracer, sample and binder; the first absorbent material portion (18) defining a first flow path for capillary flow between the sample receiving portion and the third portion including the binder, and the second absorbent material portion (17) defining a second flow path for capillary flow between the tracer receiving portion and the third portion including the binder.

5. An article as claimed in claim 4 in which the flow path between the sample receiving portion and the third portion is shorter than that between the tracer receiving portion and the third portion.

6. An article as claimed in claim 4 in which the second absorbent material portion is treated with an agent to inhibit wetting thereof to reduce the rate of flow between the tracer receiving portion and third portion.

7. An article as claimed in claim 4 in which the support includes an absorbent material (16) in contact with the third portion to receive and store any sample and tracer which flows through the third portion.

#### Patentansprüche

1. Assayverfahren zur Bestimmung eines Analyseobjektes in einer Probe, umfassend :

— die Bereitstellung eines festen Trägers (12) mit einer zu untersuchenden Probe, wobei der feste Träger einen ersten Abschnitt (14, 18) und einen zweiten Abschnitt (13, 17) und einen dritten Abschnitt (15, 16) umfaßt und der dritte Abschnitt einen Binder für das Analyseobjekt umfaßt und der erste Abschnitt des Trägers die Probe aufnimmt und der zweite Abschnitt einen Tracer aufnimmt; Bewegen des Tracers und

der Probe durch Kapillarströmung über getrennte und verschiedene Strömungswege vom zweiten und ersten Abschnitt zum dritten Abschnitt, um erstens einen Kontakt zwischen der Probe und dem Binder herzustellen, bevor der Tracer entweder mit der Probe oder dem Binder wesentlich in Berührung kommt und um dann einen Kontakt zwischen dem Tracer, dem Binder und der Probe herzustellen, um dadurch im dritten Abschnitt aus jedem jeweiligen Analyseobjekt in der Probe, dem Binder und dem Tracer einen Komplex zu bilden; und die Bestimmung des Tracers im dritten Abschnitt des Trägers oder der Tracers, der durch den dritten Abschnitt des Trägers durchgeflossen ist, um das Analyseobjekt zu bestimmen.

2. Verfahren nach Anspruch 1, bei dem der Tracer einen Liganden und einen spezifischen Marker umfaßt.

3. Verfahren nach Anspruch 2, bei dem der spezifische Marker ein Liposom ist, das eine Farbsubstanz einschließt.

4. Produktionsgegenstand für die Durchführung des Verfahrens nach Anspruch 1, umfassend :

— einen festen Träger (12) mit einem ersten (18), einem zweiten (17) und einem dritten (16) Abschnitt aus absorbierendem Material, wobei der erste Abschnitt einen Abschnitt für die Aufnahme einer Probe (14), der zweite Abschnitt einen Abschnitt für die Aufnahme eines Tracers (13) und der dritte Abschnitt einen Binder für das zu untersuchende Analyseobjekt umfaßt, wobei der dritte Abschnitt sowohl mit der Probe als auch mit dem Abschnitt für die Aufnahme des Tracers durch Kapillarströmung verbunden ist, damit eine Kapillarströmung von der Probe und dem Tracer zum dritten Abschnitt gegeben ist und ein Kontakt zwischen dem Tracer, der Probe und dem Binder gegeben ist; wobei der erste Abschnitt aus absorbierendem Material (18) einen ersten Strömungsweg für die Kapillarströmung zwischen dem Abschnitt für die Aufnahme der Probe und dem dritten Abschnitt, der den Binder umfaßt, definiert und der zweite Abschnitt aus absorbierendem Material (17), der einen zweiten Strömungsweg für die Kapillarströmung zwischen dem Abschnitt für die Aufnahme des Tracers und dem dritten Abschnitt, der den Binder umfaßt, definiert.

5. Gegenstand nach Anspruch 4, bei dem der Strömungsweg zwischen dem Abschnitt für die Aufnahme der Probe und dem dritten Abschnitt kürzer ist als der zwischen dem Abschnitt für die Aufnahme des Tracers und dem dritten Abschnitt.

6. Gegenstand nach Anspruch 4, bei dem der zweite Abschnitt aus absorbierendem Material mit einem Agens behandelt ist, damit seine Benetzung verzögert wird, um die Strömungsgeschwindigkeit zwischen dem Abschnitt für die Aufnahme des Tracers und dem dritten Abschnitt zu verringern.

7. Gegenstand nach Anspruch 4, bei dem der

Träger ein absorbierendes Material (16), das mit dem dritten Abschnitt für die Aufnahme und Speicherung der jeweiligen Probe verbunden ist und einen Tracer, der durch den dritten Abschnitt strömt, umfaßt.

## Revendications

1. Une méthode d'essai pour déterminer un analyte dans un échantillon comprenant :

la fourniture d'un support solide (12) avec un échantillon à analyser, le support solide présentant une première partie (14, 18) une deuxième partie (13, 17) et une troisième partie (15, 16), la troisième partie contenant un liant pour l'analyte, la première partie du support recevant l'échantillon et la seconde partie recevant un traceur ; le transport du traceur et de l'échantillon par écoulement capillaire par des voies d'écoulement séparées et distinctes allant des deuxième et première parties vers la troisième partie pour fournir d'abord un contact entre l'échantillon et le liant avant un contact important du traceur avec l'échantillon ou avec le liant et, ensuite, pour fournir un contact entre le traceur, le liant et l'échantillon pour donner ainsi, dans la troisième partie, un complexe de tout analyte dans l'échantillon, liant et traceur ; et la détermination du traceur dans la troisième partie du support ou du traceur qui est passé à travers la troisième partie du support pour déterminer l'analyte.

2. Une méthode telle que revendiquée dans la revendication 1, dans laquelle le traceur comprend un ligand et une marque particulière.

3. Une méthode telle que revendiquée dans la revendication 2, dans laquelle la marque particulière est un liposome contenant une substance colorée.

4. Un article manufacturé pour mettre en oeuvre la méthode de la revendication 1, comprenant :

un support solide (12) présentant une première partie (18), une deuxième partie (17) et une troisième partie constituées de matière absorbante, la première partie présentant une partie pour recevoir un échantillon (14), la deuxième partie présentant une partie pour recevoir un traceur (13), la troisième partie contenant un liant pour l'analyte à analyser, la troisième partie étant en communication par écoulement capillaire à la fois avec les parties recevant l'échantillon et le traceur pour permettre l'écoulement capillaire de l'échantillon et du traceur vers la troisième partie pour fournir un contact entre le traceur, l'échantillon et le liant ; la première partie de matière absorbante (18) définissant un premier trajet pour l'écoulement capillaire entre la partie recevant l'échantillon et la troisième partie contenant le liant, et la seconde partie de la matière absorbante (17) définissant un second trajet pour l'écoulement capillaire entre la partie recevant le traceur et la troisième partie contenant le liant.

5. Un article tel que revendiqué dans la revendication 4, dans lequel la voie d'écoulement entre la

partie recevant l'échantillon et la troisième partie est plus courte que celle entre la partie recevant le traceur et la troisième partie.

6. Un article tel que revendiqué dans la revendication 4, dans lequel la seconde partie de la matière absorbante est traitée avec un agent pour inhiber son humidification afin de réduire la vitesse de l'écoulement entre la partie recevant le traceur et la troisième partie.

7. Un article tel que revendiqué dans la revendication 4, dans lequel le support comprend une matière absorbante (16) en contact avec la troisième partie pour recevoir et stocker tout échantillon et traceur qui s'écoule à travers la troisième partie.



